

GSM/UMTS ANTENNA

Antenna GSM/UMTS flexible hexa-band, SMA(m) cable RA, 100 mm

AO-AG-FPC14SKR100

SECTRON company offers a wide portfolio of WLAN antennas with various versions differing in shape, level of gain and manner of attachment. SECTRON guarantees a compatible connection between an antenna and all antenna adaptors produced by SECTRON.




BENEFITS

- Low VSWR
- Easy installation
- Minimalist dimensions
- Flexible


Technology	GSM/UMTS
Frequency bands	850/900/1700/1800/1900/2100 MHz
Bandwidth	-
Gain	2 dBi
VSWR	<2.0: 1
Impedance	50 Ohm
Directivity	Omnidirectional
Beam angle	H 360° V 30°
Polarization	Vertical
Maximum input power	10 W
Power voltage	_
Dimensions	20 x 70 x 0.1 mm
Weight	3.9 g
Operating temperature	-20 to +80 ° C
Execution	Internal
Method of attachment	Adhesive
Cable type	Hirose 088
The cable length	100 mm
Connector type	SMA(m) 90°

DRAWING




SIMULATED GRAFS


Far-field amplitude 900 MHz -E.nsi




Far-field amplitude 900 MHz -H.nsi



Far-field amplitude 1 800 MHz-E.nsi




Far-field amplitude 1 800 MHz-H.nsi




SIMULATED GRAFS AO-AG-FPC14SKR100

Far-field amplitude 2 100 MHz -E.nsi



Far-field amplitude 2 100 MHz-H.nsi



ALL VARIANTS AO-AG-FPC14SKR100

Different connector variants or cable lengths are available on request.

CONTACTS

SECTRON s.r.o. Josefa Šavla 1271/12 709 00 Ostrava 9, Czech Republic

WWW.SECTRON.CZ

Tel.: +420 556 621 021