



GSM/UMTS ANTENNA

Antenna GSM/UMTS Connector Mount G401-1S,
180°, 2 dBi, SMA(m)

AO-AUMTS-G401-1SS

SECTRON company offers a wide portfolio of GSM/UMTS antennas with various versions differing in shape, level of gain and manner of attachment. SECTRON guarantees a compatible connection between an antenna and all antenna adaptors produced by SECTRON.


BENEFITS

- Easy installation
- Omnidirectional - suitable for moving devices
- No cable required





Technology	GSM/UMTS
Frequency bands	800/900/1700/1800/1900/2100 MHz
Bandwidth	-
Gain	2 dBi
VSWR	<2.5:1
Impedance	50 Ohm
Directivity	Omnidirectional
Beam angle	H-360°, V-30°
Polarization	Vertical
Maximum input power	10 W
Power voltage	-
Dimensions	58.9 x 9 mm
Weight	5.81 g
Operating temperature	-40 to +85 °C
Execution	External
Method of attachment	Connectro Mount
Cable type	-
The cable length	-
Connector type	SMA(m)
Certification	RoHS, ISO 9001 & ISO 14001
Material - Enclosure	TPE
Material - Connector	Dielectric – Teflon, Body : Brass – gold plated, Contact : Brass – gold plated

DRAWING




Radiation pattern [-]



VSWR [-] – Voltage standing wave ratio

AO-AUMTS-G401-1SS

**ALL VARIANTS**

Different connector variants or cable lengths are available on request.

CONTACTS