

TWN4 MULTITECH LEGIC 42*

125kHz/134.2kHz & 13.56MHz Contactless Reader/Writer

*previously known as TWN4 LEGIC NFC



TWN4 OEM PCB
Bottom View



TWN4 OEM PCB
Top View



Desktop Top View

Elatec's TWN4 Family allows users to read and write to almost any 125kHz/134.2kHz and 13.56MHz tags and/or labels. It supports all major transponders from various suppliers like ATMEL, EM, ST, MIFARE NXP, TI, HID, LEGIC, etc. and ISO standards like ISO14443A/B including layer 4 (T=CL), ISO15693, ISO18092 / ECMA-340 (NFC).



The new generation is a direct enhancement to the successful TWN3 family as it comes in the same mechanical dimensions (OEM PCB and Desktop Housing). Desktop supports host communication via USB or RS232.

Special Features:

- Powerful SDK for writing Apps which are executed directly on the reader
- Infield Upgradeable
- Direct chip-commands support
- Two onboard SAM sockets (Secure Access Module)
- CCID and PC/SC 2.01¹⁾
- Additional interfaces for OEM PCB version
Serial (logical level 3.3V, CMOS 5V tolerant), I²C, SPI²⁾, Clock/Data³⁾, Wiegand³⁾, CAN²⁾³⁾, 1-Wire²⁾
- Dedicated expansion bus for connection of LCD, mass storage, etc.
- 8 GPIOs
- Step Model Data on request

Technical Data ⁴⁾			
Frequency	125kHz, 134.2kHz (LF) / 13.56MHz (HF)		
Housing	Material ABS UL94-V0, colour black or white		
Dimensions (L x W x H)	Desktop Reader: 88mm x 56mm x 18mm / 3.5inch x 2.2inch x 0.7inch OEM Board: 76mm x 49mm x 14mm / 3.0inch x 1.9inch x 0.6inch		
Power Supply	4.3V..5.5V via USB or RS232; RS232 requires 5V external power supply; via connector CNB 3.3V +/- 5%		
Current Consumption	RF field on: 140mA typically		
Temperature Range	Operating: -25°C up to +80°C (-13°F up to +176°F) Storage: -45°C up to +85°C (-49°F up to +185°F)		
Read- / Write Distance	Up to 100mm / 4inch (depending on transponder)		
HOST Interface	USB, RS232, serial (logical level 3.3V, CMOS 5V tolerant), I ² C, SPI ²⁾ , Clock/Data ³⁾ , Wiegand ³⁾ , CAN ²⁾³⁾ , 1-Wire ²⁾		
OS Support	Windows XP, Vista, Embedded CE ²⁾ , 7(32-/64-bit), 8, 8.1, 10, Linux, Android, iOS ²⁾ , MAC OS X ²⁾		
Transmission Speed	Host: USB: Full speed (12Mbit) – RS232: up to 115.200baud	Air: up to 424kbit/s	
Modes of Operation	<ul style="list-style-type: none"> ▪ USB keyboard emulation – USB virtual COM port – Transparent (direct chip-commands support) ▪ CCID and PC/SC 2.01¹⁾ 		
Relative Humidity	5% to 95% non-condensing		
Supported Transponders	<p>Standard</p> <ul style="list-style-type: none"> ▪ 125kHz / 134.2kHz: 4100, 4102, 4200¹⁰⁾, 4050, 4150, 4450, 4550, AWID, CASI-RUSCO, HITAG 1¹¹⁾, HITAG 2¹¹⁾, HITAG S¹¹⁾, Keri, Miro, Pyramid, TIRIS/HDX, UNIQUE, FDX-B, Q5, TITAN, T55x7, ZODIAC²⁾ ▪ <u>Optionally, in consideration:</u> 4305, Cardax, IDTECK ▪ 13.56MHz: LEGIC Advant, LEGIC Prime ▪ ISO14443 A+B: compatible to part 4, MIFARE DESFire EV1, MIFARE Plus S&X, MIFARE Pro X¹²⁾, MIFARE SmartMX¹²⁾, SLE44R35⁷⁾, SLE66Rxx my-d move, PayPass¹²⁾, MIFARE Classic, MIFARE Classic EV⁹⁾, MIFARE Ultralight, MIFARE Ultralight EV⁹⁾, MIFARE Ultralight C, NTAG2xx⁹⁾, Calypso⁷⁾, CEPAS⁷⁾, Moneo⁷⁾, PicoPass¹²⁾, SRI512⁷⁾, SRT512⁷⁾ ▪ ISO15693: EM4x35¹²⁾, Tag-it, my-d vicinity¹²⁾, ICODE SLI, M24LR16/64, HID iCLASS⁵⁾, HID iCLASS SE/SR⁵⁾ ▪ ISO18092 / NFC: NFCIP-1: NFC Forum Tag Type 2-4, Sony FeliCa¹³⁾ <p>Version P</p> <p>Standard + Cotag, G-Prox⁸⁾, HID (Prox, Prox II, Duo Prox II, ISO Prox II, Micro Prox, ProxKey III), NexWatch, Indala, ioProx</p>		
Certifications	CE, R&TTE, RoHS-II compliant, FCC ²⁾		
MTBF	500.000 hours		
Weight	Approx. 20 g (without housing)		
Order Code	Standard	Version P	
OEM Board	T4DO-B	T4DO-B-P	
USB black / white	T4DT-BB2BEL / T4DT-BB2WEL	T4DT-BB2BEL-P / T4DT-BB2WEL-P	
RS232 black / white	T4DT-BR2BEL / T4DT-BR2WEL	T4DT-BR2BEL-P / T4DT-BR2WEL-P	

¹⁾In Preparation ²⁾On Request Only ³⁾External Interface Required ⁴⁾Target Specification ⁵⁾UID Only ⁶⁾Encryption Not Supported ⁷⁾UID/PUP! Only, Read/Write On Request ⁸⁾Hash Value Only ⁹⁾r/w enhanced security features on request ¹⁰⁾Only emulation of 4100,4102 ¹¹⁾Without crypto ¹²⁾r/w in direct chip command mode ¹³⁾UID + r/w public area

Accessories			
Order Code	Snap-in holder HKSI-B - black HKSI-W - white 	Bracket Holder HKBR-B - black HKBR-W - white 	CAB-B2 - USB cable 200cm/78.74inch CAB-B3 - USB cable 12cm/4.72inch CAB-B4 - USB cable 45cm/17.72inch CAB-B7 - USB cable 120cm/47.24inch CAB-M1 - USB cable mini 12cm/4.72inch CAB-M2 - USB cable mini 25cm/9.84inch CAB-R2 - RS232 cable 200cm/78.74inch
Order Code	PWA-EU - Power Supply (EU) PWA-AUS - Power Supply (AU)	PWA-US - Power Supply (US) PWA-UK - Power Supply (UK)	

Drawing/Pin Out
Refer to document DS_TWN4 Pinout & Cables

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification. Disclaimer: All names are registered trademarks. © 2015 Elatec GmbH – DocRev9 – 08/2015